

L2-Tech2018年度 東芝ライテック株式会社 認証製品リスト

型式(クラス)	形名	固有エネルギー消費効率			L2-Tech水準 (lm/W)	
		lm	W	lm/W		
ダウン ライト型	温白色、電球色、配光角 60° 超	LEKD153015LV-LD9	1,410	10.6	133.0	131.9以上
		LEKD153015LV-LS9	1,410	10.6	133.0	
		LEKD153015WWV-LD9	1,430	10.6	134.9	
		LEKD153015WWV-LS9	1,430	10.6	134.9	
		LEKD203015LV-LD9	1,780	13.4	132.8	
		LEKD203015LV-LS9	1,780	13.4	132.8	
		LEKD203015WWV-LD9	1,800	13.4	134.3	
		LEKD203015WWV-LS9	1,800	13.4	134.3	
		LEKD252014L2V-LD9	2,260	17.1	132.1	
		LEKD252014L2V-LS9	2,260	17.1	132.1	
		LEKD252014LV-LD9	2,310	17.1	135.0	
		LEKD252014LV-LS9	2,310	17.1	135.0	
		LEKD252014WWV-LD9	2,350	17.1	137.4	
		LEKD252014WWV-LS9	2,350	17.1	137.4	
温白色、電球色、 配光角30° 超 60° 以下		LEKD252015L2V-LD9	2,310	17.1	135.0	134.5以上
		LEKD252015L2V-LS9	2,310	17.1	135.0	
		LEKD252015LV-LD9	2,370	17.1	138.5	
		LEKD252015LV-LS9	2,370	17.1	138.5	
		LEKD252015WW-LD9	2,310	17.1	135.0	
		LEKD252015WW-LS9	2,310	17.1	135.0	
		LEKD252015WWV-LD9	2,400	17.1	140.3	
		LEKD252015WWV-LS9	2,400	17.1	140.3	
		LEKD252016WW-LD9	2,330	17.1	136.2	
温白色、電球色、 配光角60° 超		LEKD253014LV-LD9	2,280	17.1	133.3	131.9以上
		LEKD253014LV-LS9	2,280	17.1	133.3	
		LEKD253014WWV-LD9	2,320	17.1	135.6	
		LEKD253014WWV-LS9	2,320	17.1	135.6	
		LEKD253015L2V-LD9	2,320	17.1	135.6	
		LEKD253015L2V-LS9	2,320	17.1	135.6	
		LEKD253015LV-LD9	2,380	17.1	139.1	
昼光色、昼白色、白色、 配光角60° 超		LEKD253015NV-LD9	2,580	17.1	150.8	150.1以上
		LEKD253015NV-LS9	2,580	17.1	150.8	
温白色、電球色、 配光角60° 超		LEKD253015WW-LD9	2,270	17.1	132.7	131.9以上
		LEKD253015WW-LS9	2,270	17.1	132.7	
		LEKD253015WWV-LD9	2,410	17.1	140.9	
		LEKD253015WWV-LS9	2,410	17.1	140.9	
		LEKD253015WWY-LD9	2,300	17.4	132.1	
		LEKD253016L-LD9	2,260	17.1	132.1	
		LEKD253016L-LS9	2,260	17.1	132.1	
		LEKD253016WW-LD9	2,300	17.1	134.5	
		LEKD253016WW-LS9	2,300	17.1	134.5	
		LEKD35041WW-LD9	3,800	28.2	134.7	
		LEKD35041WWV-LD9	3,800	28.2	134.7	
		LEKD35051WW-LD9	3,800	28.2	134.7	
		LEKD35051WWV-LD9	3,800	28.2	134.7	
		LEKD35061WWV-LD9	3,800	28.2	134.7	
	LEKD35081WWV-LD9	3,800	28.2	134.7		

L2-Tech2018年度 東芝ライテック株式会社 認証製品リスト

型式(クラス)		形名	固有エネルギー消費効率			L2-Tech水準 (lm/W)
			lm	W	lm/W	
ベース スライ ト型	ストレート	LEKR423404HN-LD9	4,000	20.4	196.0	194以上
		LEKR423404HN-LS9	4,000	20.4	196.0	
		LEKT407404HN-LD9	4,000	20.4	196.0	
		LEKT407404HN-LS9	4,000	20.4	196.0	
		LEKT407404HPN-LS9	4,000	20.4	196.0	
		LEKT412404HC6N-LD9	4,000	20.4	196.0	
		LEKT412404HC6N-LS9	4,000	20.4	196.0	
		LEKT412404HC8N-LD9	4,000	20.4	196.0	
		LEKT412404HC8N-LS9	4,000	20.4	196.0	
		LEKT412404HJN-LD9	4,000	20.4	196.0	
		LEKT412404HJN-LS9	4,000	20.4	196.0	
		LEKT412404HN-LD9	4,000	20.4	196.0	
		LEKT412404HN-LS9	4,000	20.4	196.0	
		LEKT412404HPN-LS9	4,000	20.4	196.0	
		LEKT412404HYN-LD9	4,000	20.4	196.0	
		LEKT413404HN-LD9	4,000	20.4	196.0	
		LEKT413404HN-LS9	4,000	20.4	196.0	
		LEKT423404HC6N-LD9	4,000	20.4	196.0	
		LEKT423404HC6N-LS9	4,000	20.4	196.0	
		LEKT423404HC8N-LD9	4,000	20.4	196.0	
		LEKT423404HC8N-LS9	4,000	20.4	196.0	
		LEKT423404HJN-LD9	4,000	20.4	196.0	
		LEKT423404HJN-LS9	4,000	20.4	196.0	
		LEKT423404HN-LD9	4,000	20.4	196.0	
		LEKT423404HN-LS9	4,000	20.4	196.0	
		LEKT423404HPN-LS9	4,000	20.4	196.0	
		LEKT423404HYN-LD9	4,000	20.4	196.0	