

## 主な仕様と価格

## ダウンライト本体

										ダウンライト本体																
										種別	一般屋内形		軒下形													
										埋込穴径(mm)	φ 100	φ 150	φ 150													
										調光/非調光	調光/非調光兼用	調光/非調光兼用	注1 非調光													
										形名	LEDD-16002-LD9	LEDD-16001-LD9	LEDD-16901-LS9													
LED ライト エンジン (光源部)	明るさ	シリーズ	調光/ 非調光	配光(°)	光色	色温度(K)	Ra	消費 電力 (W)	形名	ダウンライト本体 希望小売価格 (円)(税別)	8,300	8,300	16,500													
										LEDライトエンジン 希望小売価格 (円)(税別)																
										コンパクト形 蛍光灯ランプ FHT24W形 器具相当	1100	非調光	広角 85	昼白色	5000	70	12.4	LEC4/12N-W11GH50	13,500	21,800 (合計)	21,800 (合計)	30,000 (合計)				
														白色	4000	80	15.2	LEC4/15W-W11GH40								
														温白色	3500	80	15.9	LEC4/16WW-W11GH35								
														電球色	3000	80	16.6	LEC4/17L-W11GH30								
														電球色	2700	80	18.8	LEC4/19L-W11GH27								
													中角 45	昼白色	5000	70	12.4	LEC4/12N-M11GH50								
														白色	4000	80	15.2	LEC4/15W-M11GH40								
														温白色	3500	80	15.9	LEC4/16WW-M11GH35								
														電球色	3000	80	16.6	LEC4/17L-M11GH30								
														電球色	2700	80	18.8	LEC4/19L-M11GH27								
												注2 調光	広角 85	昼白色	5000	70	13.0	LECF/13N-W11GHP50					16,500	24,800 (合計)	24,800 (合計)	33,000 (合計)
														白色	4000	80	16.0	LECF/16W-W11GHP40								
														温白色	3500	80	16.0	LECF/16WW-W11GHP35								
														電球色	3000	80	17.0	LECF/17L-W11GHP30								
														電球色	2700	80	19.0	LECF/19L-W11GHP27								
													中角 45	昼白色	5000	70	13.0	LECF/13N-M11GHP50								
														白色	4000	80	16.0	LECF/16W-M11GHP40								
														温白色	3500	80	16.0	LECF/16WW-M11GHP35								
	電球色	3000	80	17.0	LECF/17L-M11GHP30																					
	電球色	2700	80	19.0	LECF/19L-M11GHP27																					
	コンパクト形 蛍光灯ランプ FHT32W形 器具相当	1600	非調光	広角 85	昼白色	5000	70	18.2	LEC4/18N-W16GH50	17,500	25,800 (合計)	25,800 (合計)	34,000 (合計)													
					白色	4000	80	22.1	LEC3/22W-W16GH40																	
					温白色	3500	80	23.6	LEC3/24WW-W16GH35																	
					電球色	3000	80	23.6	LEC3/24L-W15GH30																	
					電球色	2700	80	23.6	LEC3/24L-W14GH27																	
				中角 45	昼白色	5000	70	18.2	LEC4/18N-M16GH50																	
					白色	4000	80	22.1	LEC3/22W-M16GH40																	
					温白色	3500	80	23.6	LEC3/24WW-M16GH35																	
					電球色	3000	80	23.6	LEC3/24L-M15GH30																	
					電球色	2700	80	23.6	LEC3/24L-M14GH27																	
			注2 調光	広角 85	昼白色	5000	70	19.0	LECF/19N-W16GHP50					20,500	28,800 (合計)	28,800 (合計)	37,000 (合計)									
					白色	4000	80	22.0	LECF/22W-W16GHP40																	
					温白色	3500	80	24.0	LECF/24WW-W16GHP35																	
					電球色	3000	80	24.0	LECF/24L-W15GHP30																	
					電球色	2700	80	24.0	LECF/24L-W14GHP27																	
				中角 45	昼白色	5000	70	19.0	LECF/19N-M16GHP50																	
					白色	4000	80	22.0	LECF/22W-M16GHP40																	
					温白色	3500	80	24.0	LECF/24WW-M16GHP35																	
					電球色	3000	80	24.0	LECF/24L-M15GHP30																	
					電球色	2700	80	24.0	LECF/24L-M14GHP27																	
	コンパクト形 蛍光灯ランプ FHT42W形 器具相当	2000	非調光	広角 85	昼白色	5000	70	23.6	LEC3/24N-W20GH50	21,500	29,800 (合計)	29,800 (合計)	38,000 (合計)													
				中角 45	昼白色	5000	70	23.6	LEC3/24N-M20GH50																	
			注2 調光	広角 85	昼白色	5000	70	24.0	LECF/24N-W20GHP50	24,500	32,800 (合計)	32,800 (合計)	41,000 (合計)													
				中角 45	昼白色	5000	70	24.0	LECF/24N-M20GHP50																	

電圧:100/200V

調光:約5%~100%

注1 調光用タイプのLEDライトエンジンと組合せした場合、調光はせずに100%点灯になります。

注2 調光用タイプのLEDライトエンジンは2011年11月より順次発売予定になります。