

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LER-41478K-LD9	LDL40SD/29/35-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	昼光色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SN/29/38-G2	3,380	33.5	100.8	33.0	102.4	33.0	102.4	昼白色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SW/29/37-G2	3,290	33.5	98.2	33.0	99.6	33.0	99.6	白色
2	施設用LED照明器具	LER-41478K-LD9	LDL40SWW/29/35-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	温白色
2	施設用LED照明器具	LER-41478K-LD9	LDL40SL/29/33-G2	2,940	33.5	87.7	33.0	89.0	33.0	89.0	電球色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SN/29/35P-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	昼白色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SW/29/34P-G2	3,020	33.5	90.1	33.0	91.5	33.0	91.5	白色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SD/19/23-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	昼光色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SN/19/25-G2	2,220	22.5	98.6	22.0	100.9	22.0	100.9	昼白色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SW/19/23-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	白色
2	施設用LED照明器具	LER-41478K-LD9	LDL40SWW/19/22-G2	1,950	22.5	86.6	22.0	88.6	22.0	88.6	温白色
2	施設用LED照明器具	LER-41478K-LD9	LDL40SL/19/21-G2	1,860	22.5	82.6	22.0	84.5	22.0	84.5	電球色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SN/19/23P-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	昼白色
1	施設用LED照明器具	LER-41478K-LD9	LDL40SW/19/21P-G2	1,860	22.5	82.6	22.0	84.5	22.0	84.5	白色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SD/29/35-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	昼光色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SN/29/38-G2	3,380	33.5	100.8	33.0	102.4	33.0	102.4	昼白色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SW/29/37-G2	3,290	33.5	98.2	33.0	99.6	33.0	99.6	白色
2	施設用LED照明器具	LER-41478K-LS9	LDL40SWW/29/35-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	温白色
2	施設用LED照明器具	LER-41478K-LS9	LDL40SL/29/33-G2	2,940	33.5	87.7	33.0	89.0	33.0	89.0	電球色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SN/29/35P-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	昼白色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SW/29/34P-G2	3,020	33.5	90.1	33.0	91.5	33.0	91.5	白色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SD/19/23-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	昼光色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SN/19/25-G2	2,220	22.5	98.6	22.0	100.9	22.0	100.9	昼白色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SW/19/23-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	白色
2	施設用LED照明器具	LER-41478K-LS9	LDL40SWW/19/22-G2	1,950	22.5	86.6	22.0	88.6	22.0	88.6	温白色
2	施設用LED照明器具	LER-41478K-LS9	LDL40SL/19/21-G2	1,860	22.5	82.6	22.0	84.5	22.0	84.5	電球色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SN/19/23P-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	昼白色
1	施設用LED照明器具	LER-41478K-LS9	LDL40SW/19/21P-G2	1,860	22.5	82.6	22.0	84.5	22.0	84.5	白色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SD/29/35-G2	2,910	33.5	86.8	33.0	88.1	33.0	88.1	昼光色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SN/29/38-G2	3,160	33.5	94.3	33.0	95.7	33.0	95.7	昼白色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SW/29/37-G2	3,080	33.5	91.9	33.0	93.3	33.0	93.3	白色
2	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SWW/29/35-G2	2,910	33.5	86.8	33.0	88.1	33.0	88.1	温白色
2	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SL/29/33-G2	2,740	33.5	81.7	33.0	83.0	33.0	83.0	電球色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SN/29/35P-G2	2,910	33.5	86.8	33.0	88.1	33.0	88.1	昼白色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SW/29/34P-G2	2,830	33.5	84.4	33.0	85.7	33.0	85.7	白色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SD/19/23-G2	1,910	22.5	84.8	22.0	86.8	22.0	86.8	昼光色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SN/19/25-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	昼白色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SW/19/23-G2	1,910	22.5	84.8	22.0	86.8	22.0	86.8	白色
2	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SWW/19/22-G2	1,830	22.5	81.3	22.0	83.1	22.0	83.1	温白色
2	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SL/19/21-G2	1,750	22.5	77.7	22.0	79.5	22.0	79.5	電球色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SN/19/23P-G2	1,910	22.5	84.8	22.0	86.8	22.0	86.8	昼白色
1	施設用LED照明器具	LER-41478K-LS9+R-4109	LDL40SW/19/21P-G2	1,750	22.5	77.7	22.0	79.5	22.0	79.5	白色
1	施設用LED照明器具	LER-41482-LS9	LDL40SD/29/35-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	昼光色
1	施設用LED照明器具	LER-41482-LS9	LDL40SN/29/38-G2	3,380	33.5	100.8	33.0	102.4	33.0	102.4	昼白色
1	施設用LED照明器具	LER-41482-LS9	LDL40SW/29/37-G2	3,290	33.5	98.2	33.0	99.6	33.0	99.6	白色
2	施設用LED照明器具	LER-41482-LS9	LDL40SWW/29/35-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	温白色
2	施設用LED照明器具	LER-41482-LS9	LDL40SL/29/33-G2	2,940	33.5	87.7	33.0	89.0	33.0	89.0	電球色
1	施設用LED照明器具	LER-41482-LS9	LDL40SN/29/35P-G2	3,110	33.5	92.8	33.0	94.2	33.0	94.2	昼白色
1	施設用LED照明器具	LER-41482-LS9	LDL40SW/29/34P-G2	3,020	33.5	90.1	33.0	91.5	33.0	91.5	白色
1	施設用LED照明器具	LER-41482-LS9	LDL40SD/19/23-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	昼光色
1	施設用LED照明器具	LER-41482-LS9	LDL40SN/19/25-G2	2,220	22.5	98.6	22.0	100.9	22.0	100.9	昼白色
1	施設用LED照明器具	LER-41482-LS9	LDL40SW/19/23-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	白色
2	施設用LED照明器具	LER-41482-LS9	LDL40SWW/19/22-G2	1,950	22.5	86.6	22.0	88.6	22.0	88.6	温白色
2	施設用LED照明器具	LER-41482-LS9	LDL40SL/19/21-G2	1,860	22.5	82.6	22.0	84.5	22.0	84.5	電球色
1	施設用LED照明器具	LER-41482-LS9	LDL40SN/19/23P-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	昼白色
1	施設用LED照明器具	LER-41482-LS9	LDL40SW/19/21P-G2	1,860	22.5	82.6	22.0	84.5	22.0	84.5	白色
1	施設用LED照明器具	LER-42433-LS9	LDL40SD/29/35-G2	5,040	63.5	79.3	62.0	81.2	62.0	81.2	昼光色
1	施設用LED照明器具	LER-42433-LS9	LDL40SN/29/38-G2	5,470	63.5	86.1	62.0	88.2	62.0	88.2	昼白色
1	施設用LED照明器具	LER-42433-LS9	LDL40SW/29/37-G2	5,330	63.5	83.9	62.0	85.9	62.0	85.9	白色
2	施設用LED照明器具	LER-42433-LS9	LDL40SWW/29/35-G2	5,040	63.5	79.3	62.0	81.2	62.0	81.2	温白色
2	施設用LED照明器具	LER-42433-LS9	LDL40SL/29/33-G2	4,750	63.5	74.8	62.0	76.6	62.0	76.6	電球色
1	施設用LED照明器具	LER-42433-LS9	LDL40SN/29/35P-G2	5,040	63.5	79.3	62.0	81.2	62.0	81.2	昼白色
1	施設用LED照明器具	LER-42433-LS9	LDL40SW/29/34P-G2	4,890	63.5	77.0	62.0	78.8	62.0	78.8	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LER-42433-LS9	LDL40SD/19/23-G2	3,300	41.5	79.5	41.0	80.4	41.0	80.4	昼光色
1	施設用LED照明器具	LER-42433-LS9	LDL40SN/19/25-G2	3,590	41.5	86.5	41.0	87.5	41.0	87.5	昼白色
1	施設用LED照明器具	LER-42433-LS9	LDL40SW/19/23-G2	3,300	41.5	79.5	41.0	80.4	41.0	80.4	白色
2	施設用LED照明器具	LER-42433-LS9	LDL40SWW/19/22-G2	3,160	41.5	76.1	41.0	77.0	41.0	77.0	温白色
2	施設用LED照明器具	LER-42433-LS9	LDL40SL/19/21-G2	3,020	41.5	72.7	41.0	73.6	41.0	73.6	電球色
1	施設用LED照明器具	LER-42433-LS9	LDL40SN/19/23P-G2	3,300	41.5	79.5	41.0	80.4	41.0	80.4	昼白色
1	施設用LED照明器具	LER-42433-LS9	LDL40SW/19/21P-G2	3,020	41.5	72.7	41.0	73.6	41.0	73.6	白色
1	施設用LED照明器具	LER-42438-LS9	LDL40SD/29/35-G2	5,040	63.5	79.3	62.0	81.2	62.0	81.2	昼光色
1	施設用LED照明器具	LER-42438-LS9	LDL40SN/29/38-G2	5,470	63.5	86.1	62.0	88.2	62.0	88.2	昼白色
1	施設用LED照明器具	LER-42438-LS9	LDL40SW/29/37-G2	5,330	63.5	83.9	62.0	85.9	62.0	85.9	白色
2	施設用LED照明器具	LER-42438-LS9	LDL40SWW/29/35-G2	5,040	63.5	79.3	62.0	81.2	62.0	81.2	温白色
2	施設用LED照明器具	LER-42438-LS9	LDL40SL/29/33-G2	4,750	63.5	74.8	62.0	76.6	62.0	76.6	電球色
1	施設用LED照明器具	LER-42438-LS9	LDL40SN/29/35P-G2	5,040	63.5	79.3	62.0	81.2	62.0	81.2	昼白色
1	施設用LED照明器具	LER-42438-LS9	LDL40SW/29/34P-G2	4,890	63.5	77.0	62.0	78.8	62.0	78.8	白色
1	施設用LED照明器具	LER-42438-LS9	LDL40SD/19/23-G2	3,300	41.5	79.5	41.0	80.4	41.0	80.4	昼光色
1	施設用LED照明器具	LER-42438-LS9	LDL40SN/19/25-G2	3,590	41.5	86.5	41.0	87.5	41.0	87.5	昼白色
1	施設用LED照明器具	LER-42438-LS9	LDL40SW/19/23-G2	3,300	41.5	79.5	41.0	80.4	41.0	80.4	白色
2	施設用LED照明器具	LER-42438-LS9	LDL40SWW/19/22-G2	3,160	41.5	76.1	41.0	77.0	41.0	77.0	温白色
2	施設用LED照明器具	LER-42438-LS9	LDL40SL/19/21-G2	3,020	41.5	72.7	41.0	73.6	41.0	73.6	電球色
1	施設用LED照明器具	LER-42438-LS9	LDL40SN/19/23P-G2	3,300	41.5	79.5	41.0	80.4	41.0	80.4	昼白色
1	施設用LED照明器具	LER-42438-LS9	LDL40SW/19/21P-G2	3,020	41.5	72.7	41.0	73.6	41.0	73.6	白色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SD/29/35-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	昼光色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SN/29/38-G2	6,660	63.5	104.8	62.0	107.4	62.0	107.4	昼白色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SW/29/37-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	白色
2	施設用LED照明器具	LER-42478K-LD9	LDL40SWW/29/35-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	温白色
2	施設用LED照明器具	LER-42478K-LD9	LDL40SL/29/33-G2	5,780	63.5	91.0	62.0	93.2	62.0	93.2	電球色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SN/29/35P-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	昼白色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SW/29/34P-G2	5,960	63.5	93.8	62.0	96.1	62.0	96.1	白色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SD/19/23-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	昼光色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SN/19/25-G2	4,380	41.5	105.5	41.0	106.8	41.0	106.8	昼白色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SW/19/23-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	白色
2	施設用LED照明器具	LER-42478K-LD9	LDL40SWW/19/22-G2	3,850	41.5	92.7	41.0	93.9	41.0	93.9	温白色
2	施設用LED照明器具	LER-42478K-LD9	LDL40SL/19/21-G2	3,680	41.5	88.6	41.0	89.7	41.0	89.7	電球色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SN/19/23P-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	昼白色
1	施設用LED照明器具	LER-42478K-LD9	LDL40SW/19/21P-G2	3,680	41.5	88.6	41.0	89.7	41.0	89.7	白色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SD/29/35-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	昼光色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SN/29/38-G2	6,660	63.5	104.8	62.0	107.4	62.0	107.4	昼白色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SW/29/37-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	白色
2	施設用LED照明器具	LER-42478K-LS9	LDL40SWW/29/35-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	温白色
2	施設用LED照明器具	LER-42478K-LS9	LDL40SL/29/33-G2	5,780	63.5	91.0	62.0	93.2	62.0	93.2	電球色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SN/29/35P-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	昼白色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SW/29/34P-G2	5,960	63.5	93.8	62.0	96.1	62.0	96.1	白色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SD/19/23-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	昼光色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SN/19/25-G2	4,380	41.5	105.5	41.0	106.8	41.0	106.8	昼白色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SW/19/23-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	白色
2	施設用LED照明器具	LER-42478K-LS9	LDL40SWW/19/22-G2	3,850	41.5	92.7	41.0	93.9	41.0	93.9	温白色
2	施設用LED照明器具	LER-42478K-LS9	LDL40SL/19/21-G2	3,680	41.5	88.6	41.0	89.7	41.0	89.7	電球色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SN/19/23P-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	昼白色
1	施設用LED照明器具	LER-42478K-LS9	LDL40SW/19/21P-G2	3,680	41.5	88.6	41.0	89.7	41.0	89.7	白色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SD/29/35-G2	5,780	63.5	91.0	62.0	93.2	62.0	93.2	昼光色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SN/29/38-G2	6,270	63.5	98.7	62.0	101.1	62.0	101.1	昼白色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SW/29/37-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	白色
2	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SWW/29/35-G2	5,780	63.5	91.0	62.0	93.2	62.0	93.2	温白色
2	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SL/29/33-G2	5,450	63.5	85.8	62.0	87.9	62.0	87.9	電球色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SN/29/35P-G2	5,780	63.5	91.0	62.0	93.2	62.0	93.2	昼白色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SW/29/34P-G2	5,610	63.5	88.3	62.0	90.4	62.0	90.4	白色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SD/19/23-G2	3,800	41.5	91.5	41.0	92.6	41.0	92.6	昼光色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SN/19/25-G2	4,130	41.5	99.5	41.0	100.7	41.0	100.7	昼白色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SW/19/23-G2	3,800	41.5	91.5	41.0	92.6	41.0	92.6	白色
2	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SWW/19/22-G2	3,630	41.5	87.4	41.0	88.5	41.0	88.5	温白色
2	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SL/19/21-G2	3,470	41.5	83.6	41.0	84.6	41.0	84.6	電球色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SN/19/23P-G2	3,800	41.5	91.5	41.0	92.6	41.0	92.6	昼白色
1	施設用LED照明器具	LER-42478K-LS9+R-4209	LDL40SW/19/21P-G2	3,470	41.5	83.6	41.0	84.6	41.0	84.6	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LER-42482-LS9	LDL40SD/29/35-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	昼光色
1	施設用LED照明器具	LER-42482-LS9	LDL40SN/29/38-G2	6,660	63.5	104.8	62.0	107.4	62.0	107.4	昼白色
1	施設用LED照明器具	LER-42482-LS9	LDL40SW/29/37-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	白色
2	施設用LED照明器具	LER-42482-LS9	LDL40SWW/29/35-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	温白色
2	施設用LED照明器具	LER-42482-LS9	LDL40SL/29/33-G2	5,780	63.5	91.0	62.0	93.2	62.0	93.2	電球色
1	施設用LED照明器具	LER-42482-LS9	LDL40SN/29/35P-G2	6,130	63.5	96.5	62.0	98.8	62.0	98.8	昼白色
1	施設用LED照明器具	LER-42482-LS9	LDL40SW/29/34P-G2	5,960	63.5	93.8	62.0	96.1	62.0	96.1	白色
1	施設用LED照明器具	LER-42482-LS9	LDL40SD/19/23-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	昼光色
1	施設用LED照明器具	LER-42482-LS9	LDL40SN/19/25-G2	4,380	41.5	105.5	41.0	106.8	41.0	106.8	昼白色
1	施設用LED照明器具	LER-42482-LS9	LDL40SW/19/23-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	白色
2	施設用LED照明器具	LER-42482-LS9	LDL40SWW/19/22-G2	3,850	41.5	92.7	41.0	93.9	41.0	93.9	温白色
2	施設用LED照明器具	LER-42482-LS9	LDL40SL/19/21-G2	3,680	41.5	88.6	41.0	89.7	41.0	89.7	電球色
1	施設用LED照明器具	LER-42482-LS9	LDL40SN/19/23P-G2	4,030	41.5	97.1	41.0	98.2	41.0	98.2	昼白色
1	施設用LED照明器具	LER-42482-LS9	LDL40SW/19/21P-G2	3,680	41.5	88.6	41.0	89.7	41.0	89.7	白色
1	施設用LED照明器具	LET-41007-LD9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41007-LD9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41007-LD9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41007-LD9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41007-LD9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41007-LD9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41007-LD9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41007-LD9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41007-LD9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41007-LD9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41007-LD9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41007-LD9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41007-LD9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41007-LD9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41007-LS9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41007-LS9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41007-LS9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41007-LS9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41007-LS9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41007-LS9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41007-LS9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41007-LS9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41007-LS9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41007-LS9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41007-LS9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41007-LS9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41007-LS9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41007-LS9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SD/29/35-G2	2,220	33.5	66.2	33.0	67.2	33.0	67.2	昼光色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SN/29/38-G2	2,410	33.5	71.9	33.0	73.0	33.0	73.0	昼白色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SW/29/37-G2	2,350	33.5	70.1	33.0	71.2	33.0	71.2	白色
2	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SWW/29/35-G2	2,220	33.5	66.2	33.0	67.2	33.0	67.2	温白色
2	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SL/29/33-G2	2,090	33.5	62.3	33.0	63.3	33.0	63.3	電球色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SN/29/35P-G2	2,220	33.5	66.2	33.0	67.2	33.0	67.2	昼白色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SW/29/34P-G2	2,160	33.5	64.4	33.0	65.4	33.0	65.4	白色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SD/19/23-G2	1,460	22.5	64.8	22.0	66.3	22.0	66.3	昼光色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SN/19/25-G2	1,590	22.5	70.6	22.0	72.2	22.0	72.2	昼白色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SW/19/23-G2	1,460	22.5	64.8	22.0	66.3	22.0	66.3	白色
2	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SWW/19/22-G2	1,400	22.5	62.2	22.0	63.6	22.0	63.6	温白色
2	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SL/19/21-G2	1,340	22.5	59.5	22.0	60.9	22.0	60.9	電球色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SN/19/23P-G2	1,460	22.5	64.8	22.0	66.3	22.0	66.3	昼白色
1	施設用LED照明器具	LET-41084-LS9 + HR-4183F	LDL40SW/19/21P-G2	1,340	22.5	59.5	22.0	60.9	22.0	60.9	白色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SD/29/35-G2	2,810	33.5	83.8	33.0	85.1	33.0	85.1	昼光色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SN/29/38-G2	3,050	33.5	91.0	33.0	92.4	33.0	92.4	昼白色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SW/29/37-G2	2,970	33.5	88.6	33.0	90.0	33.0	90.0	白色
2	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SWW/29/35-G2	2,810	33.5	83.8	33.0	85.1	33.0	85.1	温白色
2	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SL/29/33-G2	2,650	33.5	79.1	33.0	80.3	33.0	80.3	電球色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SN/29/35P-G2	2,810	33.5	83.8	33.0	85.1	33.0	85.1	昼白色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SW/29/34P-G2	2,730	33.5	81.4	33.0	82.7	33.0	82.7	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SD/19/23-G2	1,850	22.5	82.2	22.0	84.0	22.0	84.0	昼光色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SN/19/25-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	昼白色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SW/19/23-G2	1,850	22.5	82.2	22.0	84.0	22.0	84.0	白色
2	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SWW/19/22-G2	1,770	22.5	78.6	22.0	80.4	22.0	80.4	温白色
2	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SL/19/21-G2	1,690	22.5	75.1	22.0	76.8	22.0	76.8	電球色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SN/19/23P-G2	1,850	22.5	82.2	22.0	84.0	22.0	84.0	昼白色
1	施設用LED照明器具	LET-41084-LS9 + R-4183F	LDL40SW/19/21P-G2	1,690	22.5	75.1	22.0	76.8	22.0	76.8	白色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41084-LS9 + T-4183NM	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SD/29/35-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	昼光色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SN/29/38-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	昼白色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SW/29/37-G2	3,440	33.5	102.6	33.0	104.2	33.0	104.2	白色
2	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SWW/29/35-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	温白色
2	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SL/29/33-G2	3,070	33.5	91.6	33.0	93.0	33.0	93.0	電球色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SN/29/35P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	昼白色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SW/29/34P-G2	3,160	33.5	94.3	33.0	95.7	33.0	95.7	白色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SD/19/23-G2	2,130	22.5	94.6	22.0	96.8	22.0	96.8	昼光色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SN/19/25-G2	2,320	22.5	103.1	22.0	105.4	22.0	105.4	昼白色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SW/19/23-G2	2,130	22.5	94.6	22.0	96.8	22.0	96.8	白色
2	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SWW/19/22-G2	2,040	22.5	90.6	22.0	92.7	22.0	92.7	温白色
2	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SL/19/21-G2	1,950	22.5	86.6	22.0	88.6	22.0	88.6	電球色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SN/19/23P-G2	2,130	22.5	94.6	22.0	96.8	22.0	96.8	昼白色
1	施設用LED照明器具	LET-41085-LS9 + HR-4182N	LDL40SW/19/21P-G2	1,950	22.5	86.6	22.0	88.6	22.0	88.6	白色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SD/29/35-G2	3,390	33.5	101.1	33.0	102.7	33.0	102.7	昼光色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SN/29/38-G2	3,680	33.5	109.8	33.0	111.5	33.0	111.5	昼白色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SW/29/37-G2	3,580	33.5	106.8	33.0	108.4	33.0	108.4	白色
2	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SWW/29/35-G2	3,390	33.5	101.1	33.0	102.7	33.0	102.7	温白色
2	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SL/29/33-G2	3,200	33.5	95.5	33.0	96.9	33.0	96.9	電球色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SN/29/35P-G2	3,390	33.5	101.1	33.0	102.7	33.0	102.7	昼白色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SW/29/34P-G2	3,290	33.5	98.2	33.0	99.6	33.0	99.6	白色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SD/19/23-G2	2,230	22.5	99.1	22.0	101.3	22.0	101.3	昼光色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SN/19/25-G2	2,420	22.5	107.5	22.0	110.0	22.0	110.0	昼白色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SW/19/23-G2	2,230	22.5	99.1	22.0	101.3	22.0	101.3	白色
2	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SWW/19/22-G2	2,130	22.5	94.6	22.0	96.8	22.0	96.8	温白色
2	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SL/19/21-G2	2,030	22.5	90.2	22.0	92.2	22.0	92.2	電球色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SN/19/23P-G2	2,230	22.5	99.1	22.0	101.3	22.0	101.3	昼白色
1	施設用LED照明器具	LET-41085-LS9 + R-4182M	LDL40SW/19/21P-G2	2,030	22.5	90.2	22.0	92.2	22.0	92.2	白色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41085-LS9 + T-4182	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色



区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LET-41207NK-LD9	LDL40SD/19/23-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	昼光色
1	施設用LED照明器具	LET-41207NK-LD9	LDL40SN/19/25-G2	2,260	22.5	100.4	22.0	102.7	22.0	102.7	昼白色
1	施設用LED照明器具	LET-41207NK-LD9	LDL40SW/19/23-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	白色
2	施設用LED照明器具	LET-41207NK-LD9	LDL40SWW/19/22-G2	1,990	22.5	88.4	22.0	90.4	22.0	90.4	温白色
2	施設用LED照明器具	LET-41207NK-LD9	LDL40SL/19/21-G2	1,900	22.5	84.4	22.0	86.3	22.0	86.3	電球色
1	施設用LED照明器具	LET-41207NK-LD9	LDL40SN/19/23P-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	昼白色
1	施設用LED照明器具	LET-41207NK-LD9	LDL40SW/19/21P-G2	1,900	22.5	84.4	22.0	86.3	22.0	86.3	白色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SD/29/35-G2	3,180	33.5	94.9	33.0	96.3	33.0	96.3	昼光色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SN/29/38-G2	3,450	33.5	102.9	33.0	104.5	33.0	104.5	昼白色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SW/29/37-G2	3,360	33.5	100.2	33.0	101.8	33.0	101.8	白色
2	施設用LED照明器具	LET-41207NK-LS9	LDL40SWW/29/35-G2	3,180	33.5	94.9	33.0	96.3	33.0	96.3	温白色
2	施設用LED照明器具	LET-41207NK-LS9	LDL40SL/29/33-G2	3,000	33.5	89.5	33.0	90.9	33.0	90.9	電球色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SN/29/35P-G2	3,180	33.5	94.9	33.0	96.3	33.0	96.3	昼白色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SW/29/34P-G2	3,090	33.5	92.2	33.0	93.6	33.0	93.6	白色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SD/19/23-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	昼光色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SN/19/25-G2	2,260	22.5	100.4	22.0	102.7	22.0	102.7	昼白色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SW/19/23-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	白色
2	施設用LED照明器具	LET-41207NK-LS9	LDL40SWW/19/22-G2	1,990	22.5	88.4	22.0	90.4	22.0	90.4	温白色
2	施設用LED照明器具	LET-41207NK-LS9	LDL40SL/19/21-G2	1,900	22.5	84.4	22.0	86.3	22.0	86.3	電球色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SN/19/23P-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	昼白色
1	施設用LED照明器具	LET-41207NK-LS9	LDL40SW/19/21P-G2	1,900	22.5	84.4	22.0	86.3	22.0	86.3	白色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SD/29/35-G2	3,180	33.5	94.9	33.0	96.3	33.0	96.3	昼光色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SN/29/38-G2	3,450	33.5	102.9	33.0	104.5	33.0	104.5	昼白色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SW/29/37-G2	3,360	33.5	100.2	33.0	101.8	33.0	101.8	白色
2	施設用LED照明器具	LET-41217NK-LS9	LDL40SWW/29/35-G2	3,180	33.5	94.9	33.0	96.3	33.0	96.3	温白色
2	施設用LED照明器具	LET-41217NK-LS9	LDL40SL/29/33-G2	3,000	33.5	89.5	33.0	90.9	33.0	90.9	電球色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SN/29/35P-G2	3,180	33.5	94.9	33.0	96.3	33.0	96.3	昼白色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SW/29/34P-G2	3,090	33.5	92.2	33.0	93.6	33.0	93.6	白色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SD/19/23-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	昼光色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SN/19/25-G2	2,260	22.5	100.4	22.0	102.7	22.0	102.7	昼白色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SW/19/23-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	白色
2	施設用LED照明器具	LET-41217NK-LS9	LDL40SWW/19/22-G2	1,990	22.5	88.4	22.0	90.4	22.0	90.4	温白色
2	施設用LED照明器具	LET-41217NK-LS9	LDL40SL/19/21-G2	1,900	22.5	84.4	22.0	86.3	22.0	86.3	電球色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SN/19/23P-G2	2,080	22.5	92.4	22.0	94.5	22.0	94.5	昼白色
1	施設用LED照明器具	LET-41217NK-LS9	LDL40SW/19/21P-G2	1,900	22.5	84.4	22.0	86.3	22.0	86.3	白色
1	施設用LED照明器具	LET-41307-LD9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41307-LD9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41307-LD9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41307-LD9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41307-LD9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41307-LD9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41307-LD9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41307-LD9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41307-LD9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41307-LD9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41307-LD9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41307-LD9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41307-LD9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41307-LD9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41307-LS9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41307-LS9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41307-LS9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LET-41307P-LS9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41307P-LS9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41307P-LS9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41307P-LS9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41307P-LS9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41307P-LS9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41384-LS9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41384-LS9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41384-LS9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41384-LS9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41384-LS9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41384-LS9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41384-LS9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41384-LS9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41384-LS9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41384-LS9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41384-LS9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41384-LS9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41384-LS9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41384-LS9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SD/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼光色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/29/38-G2	3,630	33.5	108.3	33.0	110.0	33.0	110.0	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/29/37-G2	3,530	33.5	105.3	33.0	106.9	33.0	106.9	白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SWW/29/35-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	温白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SL/29/33-G2	3,150	33.5	94.0	33.0	95.4	33.0	95.4	電球色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/29/35P-G2	3,340	33.5	99.7	33.0	101.2	33.0	101.2	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/29/34P-G2	3,250	33.5	97.0	33.0	98.4	33.0	98.4	白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SD/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼光色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/19/25-G2	2,390	22.5	106.2	22.0	108.6	22.0	108.6	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/19/23-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SWW/19/22-G2	2,100	22.5	93.3	22.0	95.4	22.0	95.4	温白色
2	施設用LED照明器具	LET-41386-LS9	LDL40SL/19/21-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	電球色
1	施設用LED照明器具	LET-41386-LS9	LDL40SN/19/23P-G2	2,200	22.5	97.7	22.0	100.0	22.0	100.0	昼白色
1	施設用LED照明器具	LET-41386-LS9	LDL40SW/19/21P-G2	2,010	22.5	89.3	22.0	91.3	22.0	91.3	白色
1	施設用LED照明器具	LET-42007-LS9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42007-LS9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42007-LS9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42007-LS9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42007-LS9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42007-LS9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42007-LS9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42007-LS9	LDL40SD/19/23-G2	4,180	41.5	100.7	41.0	101.9	41.0	101.9	昼光色
1	施設用LED照明器具	LET-42007-LS9	LDL40SN/19/25-G2	4,540	41.5	109.3	41.0	110.7	41.0	110.7	昼白色
1	施設用LED照明器具	LET-42007-LS9	LDL40SW/19/23-G2	4,180	41.5	100.7	41.0	101.9	41.0	101.9	白色
2	施設用LED照明器具	LET-42007-LS9	LDL40SWW/19/22-G2	4,000	41.5	96.3	41.0	97.5	41.0	97.5	温白色
2	施設用LED照明器具	LET-42007-LS9	LDL40SL/19/21-G2	3,810	41.5	91.8	41.0	92.9	41.0	92.9	電球色
1	施設用LED照明器具	LET-42007-LS9	LDL40SN/19/23P-G2	4,180	41.5	100.7	41.0	101.9	41.0	101.9	昼白色
1	施設用LED照明器具	LET-42007-LS9	LDL40SW/19/21P-G2	3,810	41.5	91.8	41.0	92.9	41.0	92.9	白色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SD/29/35-G2	5,450	63.5	85.8	62.0	87.9	62.0	87.9	昼光色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SN/29/38-G2	5,920	63.5	93.2	62.0	95.4	62.0	95.4	昼白色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SW/29/37-G2	5,760	63.5	90.7	62.0	92.9	62.0	92.9	白色
2	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SWW/29/35-G2	5,450	63.5	85.8	62.0	87.9	62.0	87.9	温白色
2	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SL/29/33-G2	5,140	63.5	80.9	62.0	82.9	62.0	82.9	電球色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SN/29/35P-G2	5,450	63.5	85.8	62.0	87.9	62.0	87.9	昼白色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SW/29/34P-G2	5,300	63.5	83.4	62.0	85.4	62.0	85.4	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SD/19/23-G2	3,580	41.5	86.2	41.0	87.3	41.0	87.3	昼光色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SN/19/25-G2	3,890	41.5	93.7	41.0	94.8	41.0	94.8	昼白色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SW/19/23-G2	3,580	41.5	86.2	41.0	87.3	41.0	87.3	白色
2	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SWW/19/22-G2	3,420	41.5	82.4	41.0	83.4	41.0	83.4	温白色
2	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SL/19/21-G2	3,270	41.5	78.7	41.0	79.7	41.0	79.7	電球色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SN/19/23P-G2	3,580	41.5	86.2	41.0	87.3	41.0	87.3	昼白色
1	施設用LED照明器具	LET-42084-LS9 + R-4284F	LDL40SW/19/21P-G2	3,270	41.5	78.7	41.0	79.7	41.0	79.7	白色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SD/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼光色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SN/19/25-G2	4,640	41.5	111.8	41.0	113.1	41.0	113.1	昼白色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SW/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	白色
2	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SWW/19/22-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	温白色
2	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SL/19/21-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	電球色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SN/19/23P-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼白色
1	施設用LED照明器具	LET-42084-LS9 + T-4284NM	LDL40SW/19/21P-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	白色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SD/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼光色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SN/29/38-G2	6,730	63.5	105.9	62.0	108.5	62.0	108.5	昼白色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SW/29/37-G2	6,550	63.5	103.1	62.0	105.6	62.0	105.6	白色
2	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SWW/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	温白色
2	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SL/29/33-G2	5,840	63.5	91.9	62.0	94.1	62.0	94.1	電球色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SN/29/35P-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼白色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SW/29/34P-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	白色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SD/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼光色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SN/19/25-G2	4,430	41.5	106.7	41.0	108.0	41.0	108.0	昼白色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SW/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	白色
2	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SWW/19/22-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	温白色
2	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SL/19/21-G2	3,720	41.5	89.6	41.0	90.7	41.0	90.7	電球色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SN/19/23P-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼白色
1	施設用LED照明器具	LET-42085-LS9 + R-4282M	LDL40SW/19/21P-G2	3,720	41.5	89.6	41.0	90.7	41.0	90.7	白色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SD/19/23-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	昼光色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SN/19/25-G2	4,630	41.5	111.5	41.0	112.9	41.0	112.9	昼白色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SW/19/23-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	白色
2	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SWW/19/22-G2	4,070	41.5	98.0	41.0	99.2	41.0	99.2	温白色
2	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SL/19/21-G2	3,890	41.5	93.7	41.0	94.8	41.0	94.8	電球色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SN/19/23P-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	昼白色
1	施設用LED照明器具	LET-42085-LS9 + T-4282	LDL40SW/19/21P-G2	3,890	41.5	93.7	41.0	94.8	41.0	94.8	白色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SD/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼光色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SN/29/38-G2	6,730	63.5	105.9	62.0	108.5	62.0	108.5	昼白色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SW/29/37-G2	6,550	63.5	103.1	62.0	105.6	62.0	105.6	白色
2	施設用LED照明器具	LET-42107NK-LD9	LDL40SWW/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	温白色
2	施設用LED照明器具	LET-42107NK-LD9	LDL40SL/29/33-G2	5,840	63.5	91.9	62.0	94.1	62.0	94.1	電球色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SN/29/35P-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼白色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SW/29/34P-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	白色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SD/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼光色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SN/19/25-G2	4,440	41.5	106.9	41.0	108.2	41.0	108.2	昼白色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SW/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	白色
2	施設用LED照明器具	LET-42107NK-LD9	LDL40SWW/19/22-G2	3,910	41.5	94.2	41.0	95.3	41.0	95.3	温白色
2	施設用LED照明器具	LET-42107NK-LD9	LDL40SL/19/21-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	電球色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SN/19/23P-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼白色
1	施設用LED照明器具	LET-42107NK-LD9	LDL40SW/19/21P-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SD/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼光色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SN/29/38-G2	6,730	63.5	105.9	62.0	108.5	62.0	108.5	昼白色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SW/29/37-G2	6,550	63.5	103.1	62.0	105.6	62.0	105.6	白色
2	施設用LED照明器具	LET-42107NK-LS9	LDL40SWW/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	温白色
2	施設用LED照明器具	LET-42107NK-LS9	LDL40SL/29/33-G2	5,840	63.5	91.9	62.0	94.1	62.0	94.1	電球色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SN/29/35P-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼白色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SW/29/34P-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	白色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SD/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼光色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SN/19/25-G2	4,440	41.5	106.9	41.0	108.2	41.0	108.2	昼白色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SW/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	白色
2	施設用LED照明器具	LET-42107NK-LS9	LDL40SWW/19/22-G2	3,910	41.5	94.2	41.0	95.3	41.0	95.3	温白色
2	施設用LED照明器具	LET-42107NK-LS9	LDL40SL/19/21-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	電球色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SN/19/23P-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼白色
1	施設用LED照明器具	LET-42107NK-LS9	LDL40SW/19/21P-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	白色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SD/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼光色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SN/29/38-G2	6,730	63.5	105.9	62.0	108.5	62.0	108.5	昼白色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SW/29/37-G2	6,550	63.5	103.1	62.0	105.6	62.0	105.6	白色
2	施設用LED照明器具	LET-42107NP-LS9	LDL40SWW/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	温白色
2	施設用LED照明器具	LET-42107NP-LS9	LDL40SL/29/33-G2	5,840	63.5	91.9	62.0	94.1	62.0	94.1	電球色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SN/29/35P-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼白色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SW/29/34P-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	白色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SD/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼光色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SN/19/25-G2	4,440	41.5	106.9	41.0	108.2	41.0	108.2	昼白色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SW/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	白色
2	施設用LED照明器具	LET-42107NP-LS9	LDL40SWW/19/22-G2	3,910	41.5	94.2	41.0	95.3	41.0	95.3	温白色
2	施設用LED照明器具	LET-42107NP-LS9	LDL40SL/19/21-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	電球色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SN/19/23P-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼白色
1	施設用LED照明器具	LET-42107NP-LS9	LDL40SW/19/21P-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	白色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SD/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼光色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SN/29/38-G2	6,730	63.5	105.9	62.0	108.5	62.0	108.5	昼白色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SW/29/37-G2	6,550	63.5	103.1	62.0	105.6	62.0	105.6	白色
2	施設用LED照明器具	LET-42117NK-LS9	LDL40SWW/29/35-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	温白色
2	施設用LED照明器具	LET-42117NK-LS9	LDL40SL/29/33-G2	5,840	63.5	91.9	62.0	94.1	62.0	94.1	電球色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SN/29/35P-G2	6,200	63.5	97.6	62.0	100.0	62.0	100.0	昼白色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SW/29/34P-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	白色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SD/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼光色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SN/19/25-G2	4,440	41.5	106.9	41.0	108.2	41.0	108.2	昼白色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SW/19/23-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	白色
2	施設用LED照明器具	LET-42117NK-LS9	LDL40SWW/19/22-G2	3,910	41.5	94.2	41.0	95.3	41.0	95.3	温白色
2	施設用LED照明器具	LET-42117NK-LS9	LDL40SL/19/21-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	電球色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SN/19/23P-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	昼白色
1	施設用LED照明器具	LET-42117NK-LS9	LDL40SW/19/21P-G2	3,730	41.5	89.8	41.0	90.9	41.0	90.9	白色
1	施設用LED照明器具	LET-42307-LD9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42307-LD9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42307-LD9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42307-LD9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42307-LD9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42307-LD9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42307-LD9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42307-LD9	LDL40SD/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼光色
1	施設用LED照明器具	LET-42307-LD9	LDL40SN/19/25-G2	4,640	41.5	111.8	41.0	113.1	41.0	113.1	昼白色
1	施設用LED照明器具	LET-42307-LD9	LDL40SW/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	白色
2	施設用LED照明器具	LET-42307-LD9	LDL40SWW/19/22-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	温白色
2	施設用LED照明器具	LET-42307-LD9	LDL40SL/19/21-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	電球色
1	施設用LED照明器具	LET-42307-LD9	LDL40SN/19/23P-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼白色
1	施設用LED照明器具	LET-42307-LD9	LDL40SW/19/21P-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	白色
1	施設用LED照明器具	LET-42307-LS9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42307-LS9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42307-LS9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42307-LS9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42307-LS9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42307-LS9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42307-LS9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LET-42307-LS9	LDL40SD/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼光色
1	施設用LED照明器具	LET-42307-LS9	LDL40SN/19/25-G2	4,640	41.5	111.8	41.0	113.1	41.0	113.1	昼白色
1	施設用LED照明器具	LET-42307-LS9	LDL40SW/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	白色
2	施設用LED照明器具	LET-42307-LS9	LDL40SWW/19/22-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	温白色
2	施設用LED照明器具	LET-42307-LS9	LDL40SL/19/21-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	電球色
1	施設用LED照明器具	LET-42307-LS9	LDL40SN/19/23P-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼白色
1	施設用LED照明器具	LET-42307-LS9	LDL40SW/19/21P-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	白色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42307P-LS9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42307P-LS9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SD/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼光色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SN/19/25-G2	4,640	41.5	111.8	41.0	113.1	41.0	113.1	昼白色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SW/19/23-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	白色
2	施設用LED照明器具	LET-42307P-LS9	LDL40SWW/19/22-G2	4,080	41.5	98.3	41.0	99.5	41.0	99.5	温白色
2	施設用LED照明器具	LET-42307P-LS9	LDL40SL/19/21-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	電球色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SN/19/23P-G2	4,270	41.5	102.8	41.0	104.1	41.0	104.1	昼白色
1	施設用LED照明器具	LET-42307P-LS9	LDL40SW/19/21P-G2	3,900	41.5	93.9	41.0	95.1	41.0	95.1	白色
1	施設用LED照明器具	LET-42384-LS9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42384-LS9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42384-LS9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42384-LS9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42384-LS9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42384-LS9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42384-LS9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42384-LS9	LDL40SD/19/23-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	昼光色
1	施設用LED照明器具	LET-42384-LS9	LDL40SN/19/25-G2	4,630	41.5	111.5	41.0	112.9	41.0	112.9	昼白色
1	施設用LED照明器具	LET-42384-LS9	LDL40SW/19/23-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	白色
2	施設用LED照明器具	LET-42384-LS9	LDL40SWW/19/22-G2	4,070	41.5	98.0	41.0	99.2	41.0	99.2	温白色
2	施設用LED照明器具	LET-42384-LS9	LDL40SL/19/21-G2	3,890	41.5	93.7	41.0	94.8	41.0	94.8	電球色
1	施設用LED照明器具	LET-42384-LS9	LDL40SN/19/23P-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	昼白色
1	施設用LED照明器具	LET-42384-LS9	LDL40SW/19/21P-G2	3,890	41.5	93.7	41.0	94.8	41.0	94.8	白色
1	施設用LED照明器具	LET-42386-LS9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42386-LS9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42386-LS9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42386-LS9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42386-LS9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42386-LS9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42386-LS9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42386-LS9	LDL40SD/19/23-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	昼光色
1	施設用LED照明器具	LET-42386-LS9	LDL40SN/19/25-G2	4,630	41.5	111.5	41.0	112.9	41.0	112.9	昼白色
1	施設用LED照明器具	LET-42386-LS9	LDL40SW/19/23-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	白色
2	施設用LED照明器具	LET-42386-LS9	LDL40SWW/19/22-G2	4,070	41.5	98.0	41.0	99.2	41.0	99.2	温白色
2	施設用LED照明器具	LET-42386-LS9	LDL40SL/19/21-G2	3,890	41.5	93.7	41.0	94.8	41.0	94.8	電球色
1	施設用LED照明器具	LET-42386-LS9	LDL40SN/19/23P-G2	4,260	41.5	102.6	41.0	103.9	41.0	103.9	昼白色
1	施設用LED照明器具	LET-42386-LS9	LDL40SW/19/21P-G2	3,890	41.5	93.7	41.0	94.8	41.0	94.8	白色
1	施設用LED照明器具	LET-42404-LD9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42404-LD9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42404-LD9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42404-LD9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42404-LD9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42404-LD9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42404-LD9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42404-LD9	LDL40SD/19/23-G2	4,250	41.5	102.4	41.0	103.6	41.0	103.6	昼光色
1	施設用LED照明器具	LET-42404-LD9	LDL40SN/19/25-G2	4,620	41.5	111.3	41.0	112.6	41.0	112.6	昼白色
1	施設用LED照明器具	LET-42404-LD9	LDL40SW/19/23-G2	4,250	41.5	102.4	41.0	103.6	41.0	103.6	白色
2	施設用LED照明器具	LET-42404-LD9	LDL40SWW/19/22-G2	4,070	41.5	98.0	41.0	99.2	41.0	99.2	温白色
2	施設用LED照明器具	LET-42404-LD9	LDL40SL/19/21-G2	3,880	41.5	93.4	41.0	94.6	41.0	94.6	電球色
1	施設用LED照明器具	LET-42404-LD9	LDL40SN/19/23P-G2	4,250	41.5	102.4	41.0	103.6	41.0	103.6	昼白色
1	施設用LED照明器具	LET-42404-LD9	LDL40SW/19/21P-G2	3,880	41.5	93.4	41.0	94.6	41.0	94.6	白色

区分	品名	器具形名	組合せランプ形名	定格光束 (lm)	入力100V時		入力200V時		入力242V時		光源色
					定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	定格消費電力 (W)	固有エネルギー消費効率 (lm/W)	
1	施設用LED照明器具	LET-42404-LS9	LDL40SD/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼光色
1	施設用LED照明器具	LET-42404-LS9	LDL40SN/29/38-G2	7,040	63.5	110.8	62.0	113.5	62.0	113.5	昼白色
1	施設用LED照明器具	LET-42404-LS9	LDL40SW/29/37-G2	6,850	63.5	107.8	62.0	110.4	62.0	110.4	白色
2	施設用LED照明器具	LET-42404-LS9	LDL40SWW/29/35-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	温白色
2	施設用LED照明器具	LET-42404-LS9	LDL40SL/29/33-G2	6,110	63.5	96.2	62.0	98.5	62.0	98.5	電球色
1	施設用LED照明器具	LET-42404-LS9	LDL40SN/29/35P-G2	6,480	63.5	102.0	62.0	104.5	62.0	104.5	昼白色
1	施設用LED照明器具	LET-42404-LS9	LDL40SW/29/34P-G2	6,300	63.5	99.2	62.0	101.6	62.0	101.6	白色
1	施設用LED照明器具	LET-42404-LS9	LDL40SD/19/23-G2	4,250	41.5	102.4	41.0	103.6	41.0	103.6	昼光色
1	施設用LED照明器具	LET-42404-LS9	LDL40SN/19/25-G2	4,620	41.5	111.3	41.0	112.6	41.0	112.6	昼白色
1	施設用LED照明器具	LET-42404-LS9	LDL40SW/19/23-G2	4,250	41.5	102.4	41.0	103.6	41.0	103.6	白色
2	施設用LED照明器具	LET-42404-LS9	LDL40SWW/19/22-G2	4,070	41.5	98.0	41.0	99.2	41.0	99.2	温白色
2	施設用LED照明器具	LET-42404-LS9	LDL40SL/19/21-G2	3,880	41.5	93.4	41.0	94.6	41.0	94.6	電球色
1	施設用LED照明器具	LET-42404-LS9	LDL40SN/19/23P-G2	4,250	41.5	102.4	41.0	103.6	41.0	103.6	昼白色
1	施設用LED照明器具	LET-42404-LS9	LDL40SW/19/21P-G2	3,880	41.5	93.4	41.0	94.6	41.0	94.6	白色
1	施設用LED照明器具	LET-42414-LD9	LDL40SD/29/35-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	昼光色
1	施設用LED照明器具	LET-42414-LD9	LDL40SN/29/38-G2	6,540	63.5	102.9	62.0	105.4	62.0	105.4	昼白色
1	施設用LED照明器具	LET-42414-LD9	LDL40SW/29/37-G2	6,370	63.5	100.3	62.0	102.7	62.0	102.7	白色
2	施設用LED照明器具	LET-42414-LD9	LDL40SWW/29/35-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	温白色
2	施設用LED照明器具	LET-42414-LD9	LDL40SL/29/33-G2	5,680	63.5	89.4	62.0	91.6	62.0	91.6	電球色
1	施設用LED照明器具	LET-42414-LD9	LDL40SN/29/35P-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	昼白色
1	施設用LED照明器具	LET-42414-LD9	LDL40SW/29/34P-G2	5,850	63.5	92.1	62.0	94.3	62.0	94.3	白色
1	施設用LED照明器具	LET-42414-LD9	LDL40SD/19/23-G2	3,960	41.5	95.4	41.0	96.5	41.0	96.5	昼光色
1	施設用LED照明器具	LET-42414-LD9	LDL40SN/19/25-G2	4,300	41.5	103.6	41.0	104.8	41.0	104.8	昼白色
1	施設用LED照明器具	LET-42414-LD9	LDL40SW/19/23-G2	3,960	41.5	95.4	41.0	96.5	41.0	96.5	白色
2	施設用LED照明器具	LET-42414-LD9	LDL40SWW/19/22-G2	3,780	41.5	91.0	41.0	92.1	41.0	92.1	温白色
2	施設用LED照明器具	LET-42414-LD9	LDL40SL/19/21-G2	3,610	41.5	86.9	41.0	88.0	41.0	88.0	電球色
1	施設用LED照明器具	LET-42414-LD9	LDL40SN/19/23P-G2	3,960	41.5	95.4	41.0	96.5	41.0	96.5	昼白色
1	施設用LED照明器具	LET-42414-LD9	LDL40SW/19/21P-G2	3,610	41.5	86.9	41.0	88.0	41.0	88.0	白色
1	施設用LED照明器具	LET-42414-LS9	LDL40SD/29/35-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	昼光色
1	施設用LED照明器具	LET-42414-LS9	LDL40SN/29/38-G2	6,540	63.5	102.9	62.0	105.4	62.0	105.4	昼白色
1	施設用LED照明器具	LET-42414-LS9	LDL40SW/29/37-G2	6,370	63.5	100.3	62.0	102.7	62.0	102.7	白色
2	施設用LED照明器具	LET-42414-LS9	LDL40SWW/29/35-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	温白色
2	施設用LED照明器具	LET-42414-LS9	LDL40SL/29/33-G2	5,680	63.5	89.4	62.0	91.6	62.0	91.6	電球色
1	施設用LED照明器具	LET-42414-LS9	LDL40SN/29/35P-G2	6,020	63.5	94.8	62.0	97.0	62.0	97.0	昼白色
1	施設用LED照明器具	LET-42414-LS9	LDL40SW/29/34P-G2	5,850	63.5	92.1	62.0	94.3	62.0	94.3	白色
1	施設用LED照明器具	LET-42414-LS9	LDL40SD/19/23-G2	3,960	41.5	95.4	41.0	96.5	41.0	96.5	昼光色
1	施設用LED照明器具	LET-42414-LS9	LDL40SN/19/25-G2	4,300	41.5	103.6	41.0	104.8	41.0	104.8	昼白色
1	施設用LED照明器具	LET-42414-LS9	LDL40SW/19/23-G2	3,960	41.5	95.4	41.0	96.5	41.0	96.5	白色
2	施設用LED照明器具	LET-42414-LS9	LDL40SWW/19/22-G2	3,780	41.5	91.0	41.0	92.1	41.0	92.1	温白色
2	施設用LED照明器具	LET-42414-LS9	LDL40SL/19/21-G2	3,610	41.5	86.9	41.0	88.0	41.0	88.0	電球色
1	施設用LED照明器具	LET-42414-LS9	LDL40SN/19/23P-G2	3,960	41.5	95.4	41.0	96.5	41.0	96.5	昼白色
1	施設用LED照明器具	LET-42414-LS9	LDL40SW/19/21P-G2	3,610	41.5	86.9	41.0	88.0	41.0	88.0	白色
1	施設用LED照明器具	LET-42433-LS9	LDL40SD/29/35-G2	6,390	63.5	100.6	62.0	103.0	62.0	103.0	昼光色
1	施設用LED照明器具	LET-42433-LS9	LDL40SN/29/38-G2	6,940	63.5	109.2	62.0	111.9	62.0	111.9	昼白色
1	施設用LED照明器具	LET-42433-LS9	LDL40SW/29/37-G2	6,760	63.5	106.4	62.0	109.0	62.0	109.0	白色
2	施設用LED照明器具	LET-42433-LS9	LDL40SWW/29/35-G2	6,390	63.5	100.6	62.0	103.0	62.0	103.0	温白色
2	施設用LED照明器具	LET-42433-LS9	LDL40SL/29/33-G2	6,030	63.5	94.9	62.0	97.2	62.0	97.2	電球色
1	施設用LED照明器具	LET-42433-LS9	LDL40SN/29/35P-G2	6,390	63.5	100.6	62.0	103.0	62.0	103.0	昼白色
1	施設用LED照明器具	LET-42433-LS9	LDL40SW/29/34P-G2	6,210	63.5	97.7	62.0	100.1	62.0	100.1	白色
1	施設用LED照明器具	LET-42433-LS9	LDL40SD/19/23-G2	4,200	41.5	101.2	41.0	102.4	41.0	102.4	昼光色
1	施設用LED照明器具	LET-42433-LS9	LDL40SN/19/25-G2	4,560	41.5	109.8	41.0	111.2	41.0	111.2	昼白色
1	施設用LED照明器具	LET-42433-LS9	LDL40SW/19/23-G2	4,200	41.5	101.2	41.0	102.4	41.0	102.4	白色
2	施設用LED照明器具	LET-42433-LS9	LDL40SWW/19/22-G2	4,010	41.5	96.6	41.0	97.8	41.0	97.8	温白色
2	施設用LED照明器具	LET-42433-LS9	LDL40SL/19/21-G2	3,830	41.5	92.2	41.0	93.4	41.0	93.4	電球色
1	施設用LED照明器具	LET-42433-LS9	LDL40SN/19/23P-G2	4,200	41.5	101.2	41.0	102.4	41.0	102.4	昼白色
1	施設用LED照明器具	LET-42433-LS9	LDL40SW/19/21P-G2	3,830	41.5	92.2	41.0	93.4	41.0	93.4	白色
1	施設用LED照明器具	LET-42580-LS9	LDL40SD/29/35-G2	4,750	63.5	74.8	62.0	76.6	62.0	76.6	昼光色
1	施設用LED照明器具	LET-42580-LS9	LDL40SN/29/38-G2	5,160	63.5	81.2	62.0	83.2	62.0	83.2	昼白色
1	施設用LED照明器具	LET-42580-LS9	LDL40SW/29/37-G2	5,020	63.5	79.0	62.0	80.9	62.0	80.9	白色
2	施設用LED照明器具	LET-42580-LS9	LDL40SWW/29/35-G2	4,750	63.5	74.8	62.0	76.6	62.0	76.6	温白色
2	施設用LED照明器具	LET-42580-LS9	LDL40SL/29/33-G2	4,480	63.5	70.5	62.0	72.2	62.0	72.2	電球色
1	施設用LED照明器具	LET-42580-LS9	LDL40SN/29/35P-G2	4,750	63.5	74.8	62.0	76.6	62.0	76.6	昼白色
1	施設用LED照明器具	LET-42580-LS9	LDL40SW/29/34P-G2	4,620	63.5	72.7	62.0	74.5	62.0	74.5	白色

